



Firma



Sanwald

10.05.2006 14:53:08

MtB/EMG3

249

Seite 1/1



Einzelwerte:	01. 0.96	02. 0.94	03. 0.94	04. 0.93	05. 0.95	06. 0.97	07. 0.97	08. 0.94	09. 0.94	10. 0.94
	11. 0.94	12. 0.92	13. 0.94	14. 0.93	15. 0.94	16. 0.95	17. 0.94	18. 0.92	19. 0.94	20. 0.93
	21. 0.93	22. 0.95	23. 0.93	24. 0.92	25. 0.94	26. 0.93	27. 0.92	28. 0.94	29. 0.93	30. 0.93
	31. 0.93	32. 0.93	33. 0.93	34. 0.95	35. 0.92	36. 0.92	37. 0.94	38. 0.94	39. 0.93	40. 0.94
	41. 0.93	42. 0.92	43. 0.93	44. 0.92	45. 0.92	46. 0.93	47. 0.92	48. 0.92	49. 0.94	50. 0.92
	51. 0.94	52. 0.93	53. 0.93	54. 0.92	55. 0.94	56. 0.92	57. 0.92	58. 0.94	59. 0.92	60. 0.93
	61. 0.93	62. 0.93	63. 0.93	64. 0.94	65. 0.92	66. 0.92	67. 0.93	68. 0.92	69. 0.92	70. 0.94
	71. 0.93	72. 0.93	73. 0.95	74. 0.92	75. 0.93	76. 0.95	77. 0.93	78. 0.94	79. 0.94	80. 0.92
	81. 0.93	82. 0.96	83. 0.90	84. 0.93	85. 0.93	86. 0.93	87. 0.91	88. 0.94	89. 0.92	90. 0.92
	91. 0.93	92. 0.92	93. 0.92	94. 0.94	95. 0.94	96. 0.93	97. 0.94	98. 0.93	99. 0.92	100. 0.93

- E 682 000 107 - 0.50-3.50 Nm - 0.00 -0 602 495 200 -Bosch -Schrauber (allg.)

MFU vom 10.05.2006 auf BLM3850 (3860SK.055 -) Zelle/Kanal 1

Einheit: MD [Nm]Anzahl Messwerte: 1Mittelwert (x-quer): Standardabweichung: 0.01 Cm: 2.76

Cmk: 2.38

i. O.

Normalverteilung

Toleranz

Sollwert

Mittelwert (x-quer):

6s (x ± 3 s)